Federal Railroad Administration, DOT

229.101 Engines.

safety.

STEAM GENERATORS
229.103 Safe working pressure; factor of

CABS AND CAB EQUIPMENT

229.119 Cabs, floors, and passageways.

229.121 Locomotive cab noise. 229.123 Pilots, snowplows, end plates.

229.125 Headlights and auxiliary lights.

229.105 Steam generator number.

229.107 Pressure gauge.

229.113 Warning notice.

229.115 Slip/slide alarms.

229.117 Speed indicators.

229.109 Safety valves.229.111 Water-flow indicator.

§ 229.3

reaeral Railroad Administration, DOI	9229.3
Subpart C—Safety Requirements	229.127 Cab lights.
GENERAL REQUIREMENTS	229.129 Locomotive horn. 229.131 Sanders.
229.41 Protection against personal injury.229.43 Exhaust and battery gases.229.45 General condition.	229.133 Interim locomotive conspicuity measures—auxiliary external lights. 229.135 Event recorders. 229.137 Sanitation, general requirements.
Brake System	229.139 Sanitation, servicing requirements.
229.46 Brakes: General. 229.47 Emergency brake valve. 229.49 Main reservoir system.	Subpart D—Locomotive Crashworthiness Design Requirements
229.51 Aluminum main reservoirs. 229.53 Brake gauges. 229.55 Piston travel. 229.57 Foundation brake gear. 229.59 Leakage.	229.141 Body structure, MU locomotives. 229.201 Purpose and scope. 229.203 Applicability. 229.205 General requirements. 229.206 Design requirements. 229.207 New locomotive crashworthiness de-
DRAFT SYSTEM	sign standards and changes to existing
229.61 Draft system. Suspension System	FRA-approved locomotive crash- worthiness design standards.
229.63 Lateral motion. 229.64 Plain bearings. 229.65 Spring rigging. 229.67 Trucks.	229.209 Alternative locomotive crash- worthiness designs. 229.211 Processing of petitions. 229.213 Locomotive manufacturing informa- tion.
229.69 Side bearings. 229.71 Clearance above top of rail. 229.73 Wheel sets. 229.75 Wheel and tire defects.	229.215 Retention and inspection of designs. 229.217 Fuel tank. APPENDIX A TO PART 229—FORM FRA 6180—49A [NOTE]
ELECTRICAL SYSTEM 229.77 Current collectors. 229.79 Third rail shoes. 229.81 Emergency pole; shoe insulation. 229.83 Insulation or grounding of metal parts. 229.85 Doors and cover plates marked "Danger". 229.87 Hand-operated switches. 229.89 Jumpers; cable connections. 229.91 Motors and generators.	APPENDIX B TO PART 229—SCHEDULE OF CIVIL PENALITIES APPENDIX C TO PART 229—FRA LOCOMOTIVE STANDARDS—CODE OF DEFECTS [NOTE] APPENDIX D TO PART 229—CRITERIA FOR CERTIFICATION OF CRASHWORTHY EVENT RECORDER MEMORY MODULE APPENDIX E TO PART 229—PERFORMANCE CRITERIA FOR LOCOMOTIVE CRASHWORTHINESS APPENDIXES F-G TO PART 229 [RESERVED] APPENDIX H TO PART 229—STATIC NOISE TEST PROTOCOLS—IN-CAB STATIC
INTERNAL COMBUSTION EQUIPMENT 229.93 Safety cut-off device. 229.95 Venting.	AUTHORITY: 49 U.S.C. 20103, 20107, 20133, 20137–38, 20143, 20701–03, 21301–02, 21304; 28 U.S.C. 2401, note; and 49 CFR 1.49(c), (m).
229.97 Grounding fuel tanks. 229.99 Safety hangers.	SOURCE: 45 FR 21109, Mar. 31, 1980, unless otherwise noted.

Subpart A—General

§ 229.1 Scope.

This part prescribes minimum Federal safety standards for all locomotives except those propelled by steam power.

§ 229.3 Applicability.

- (a) Except as provided in paragraphs (b) through (e) of this section, this part applies to all standard gage railroads.
 - (b) This part does not apply to:
- (1) A railroad that operates only on track inside an installation which is

441